

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A communication method used in a wireless communication system which includes both a repeater relay station of a wireless communication network using repeater system and a frequency division multiple access (FDMA) relay station of a wireless communication network using FDMA system, the method comprising the steps of:

receiving a call signal from a repeater wireless terminal in the wireless communication network using repeater system, by the repeater relay station;

connecting the repeater relay station to the FDMA relay station by a line to forward the call signal received by the repeater relay station to the FDMA relay station;

setting the forwarded call signal for a control signal at the FDMA relay station;

transmitting the control signal to an FDMA wireless terminal in the wireless communication network using FDMA system; and

performing communication via the repeater relay station between the FDMA wireless terminal having received the control signal and the repeater wireless terminal, wherein the call signal to be transmitted from the repeater wireless terminal to the repeater relay station, the call signal to be transmitted from the repeater relay station to the FDMA relay station and the call signal to be transmitted from the FDMA relay station to the FDMA wireless terminal are carried by using respective distinct signal formats, and

wherein the FDMA wireless terminal operates to detect on the basis of the received control signal that the call signal is from the repeater wireless terminal and a downlink frequency f2 of the repeater relay station so that the FDMA wireless terminal switches its own reception frequency from a downlink frequency f3 of the FDMA relay station to the downlink frequency f2 of the repeater relay station.

2. (Currently Amended) A wireless communication system which includes both a repeater relay station of a wireless communication network using repeater system and an FDMA relay station of a wireless communication network using FDMA system, the system comprising:

means for receiving a call signal from a repeater wireless terminal in the wireless communication network using repeater system, by the repeater relay station;

means for forwarding the call signal received by the repeater relay station to the FDMA relay station connected to the repeater relay station by a line;

means for setting the forwarded call signal for a control signal at the FDMA relay station;

means for transmitting the control signal to an FDMA wireless terminal in the wireless communication network using FDMA system; and

means for the FDMA wireless terminal, which has received the control signal, to communicate with the repeater wireless terminal via the repeater relay station, wherein the call signal to be transmitted from the repeater wireless terminal to the repeater relay station, the call signal to be transmitted from the repeater relay station to the FDMA relay station and the call signal to be transmitted from the FDMA relay station to the FDMA wireless terminal are carried by using respective distinct signal formats, and

wherein the FDMA wireless terminal operates to detect on the basis of the received control signal that the call signal is from the repeater wireless terminal and a downlink frequency f2 of the repeater relay station so that the FDMA wireless terminal switches its own reception frequency from a downlink frequency f3 of the FDMA relay station to the downlink frequency f2 of the repeater relay station.

3. (Currently Amended) An FDMA wireless terminal to be used in a business wireless communication system which includes both a repeater relay station of a wireless communication network using repeater system and an FDMA relay station of a wireless communication network using FDMA system,

wherein the repeater relay station and the FDMA relay station are connected to each other by a line, the FDMA relay station sets a call signal from a repeater wireless terminal in the wireless communication network using repeater system, which has been forwarded from the repeater relay station, for a control signal; and

the FDMA wireless terminal in the wireless communication network using FDMA system has means for receiving the control signal sent thereto to communicate with the repeater wireless terminal via the repeater relay station, wherein the call signal to be transmitted from the repeater wireless terminal to the repeater relay station, the call signal to be transmitted from the repeater relay station to the FDMA relay station and the call signal to be transmitted from the FDMA relay station to the FDMA wireless terminal are carried by using respective distinct signal formats, and

wherein the FDMA wireless terminal operates to detect on the basis of the received control signal that the call signal is from the repeater wireless terminal and a downlink frequency f_2 of the repeater relay station so that the FDMA wireless terminal switches its own reception frequency from a downlink frequency f_3 of the FDMA relay station to the downlink frequency f_2 of the repeater relay station.

4. (Previously Presented) The communication method according to claim 1, wherein the signal format for the call signal from the repeater wireless terminal to the repeater relay station comprises a call classifier and a terminal identifier, the signal format for the call signal from the repeater relay station to the FDMA relay station comprises a synchronous signal pattern, a call classifier, a terminal identifier, a relay station identifier and information added by relay station, and the format for the call signal from the FDMA relay station to the FDMA wireless terminal comprises a synchronous signal pattern, system information and terminal control information.